

## PICTURESQUE+ 4303

**Picturesque+ 4303** is our range of textured, 2x1 weave screen fabrics, made from PVC coated polyester and available in 22 colours across a broad palette. Our **Picturesque+ 4303** has been designed to offer customers a quality screen range at an optimum price.

### TECHNICAL SPECIFICATIONS

- Composition: 30% polyester, 70% PVC
- Mesh/inch (25.4mm): 52 x 48
- Weave: 2 x 1
- Openness: 3%
- Fabric weight: 410gsm +/-5%
- Thickness: 0.60mm +/-5%
- Roll widths 250cm and 320cm (see table below).

Product codes by colour and width (where available) are outlined below:

COLOUR	WIDTH	
	250CM	320CM
White	71314010	71316010
White/Stone	71314092	71316092
White/Linen	71314095	71316095
Charcoal Apricot	71314892	71316892
Charcoal/Sand	71314893	71316893
Charcoal Grey	71314894	71316894
Charcoal Bronze	71314896	71316896
Linen		71316720
Bronze		71316780
Grey		71316830
Charcoal		71316840

### ROLL LENGTHS

Roll lengths will vary due to the manufacturing process used for this fabric. The nominal roll lengths for each width are shown below. Roll length can vary by +/- 5LM from nominal length.

- 2.5m wide rolls - nominally 25LM
- 3.2m wide rolls - nominally 20LM

### FR PROPERTIES

FR rating to AS1530Pt3:

- Ignitability Index 14
- Spread of Flame Index 0
- Heat Evolved Index 1
- Smoke Developed Index 7

### POINT-OF-SALE SUPPORT

An integrated swatch of the Copaco **Picturesque+ 4303** and **SunBloc** ranges is available to manufacturers in quantity for their own use or for distribution to their retail customer base.



## FABRICATION REQUIREMENTS

There are no special considerations for fabricators when using **Picturesque+ 4303**, except that good quality cutting techniques should be used. It is recommended that **Picturesque+ 4303** is cut using either crush cutting or ultrasonic cutting machinery. Of course, the performance of the fabric will ultimately be determined by the ability of the hardware system to adequately support the fabric with minimum bending and general deformation of the roller tube, especially in wide width installations.

## CUT-TO-LENGTH SERVICE

**Picturesque+ 4303** is available in cut lengths at a surcharge of \$10.00 per cut. Cut lengths are generally despatched within two working days of order and are available for shipment to all parts of Australia.

## KEY SELLING FEATURES

**Picturesque+ 4303** range has several features that provide competitive advantage over other screen fabric ranges sold in Australia. In particular:

- 12 fast moving colours;
- roll widths of 250cm and 320cm make for maximum cutting efficiency;
- FR rating to AS1530 Pt3;
- 5-year manufacturer's warranty; and
- cost competitive, when compared with fibreglass screens.

## PRODUCT WARRANTY

**Picturesque+ 4303** is provided with a 5-year manufacturer's warranty, supported directly by Copaco and including for internal and external applications, except when used not in accordance with the manufacturers specifications and when used in tension systems.



Blindware Pty Ltd  
Unit 1/3 Dunlop Crt, Bayswater 3153 Tel: (03) 9876 0400  
Fax: (03) 9720 2746  
Email: sales@blindware.com.au  
Web: www.blindware.com.au

## ENERGY RATINGS

Energetic and light technical properties (European Standard EN14501)

Glazing A = clear single glazing 4 mm.....Gv = 0.85

Glazing B = clear double glazing (4/12/4), space filled with air .....Gv = 0.76

Glazing C = double glazing (4/16/4), with a low emissivity coating in position 3, space filled with argon .....Gv = 0.59

Glazing D = reflective double glazing (4/16/4), with a low emissivity coating in position 2, space filled with argon.....Gv = 0.32

Picturesque+ 4303	Solar Energy properties					Visual Properties		Fabric + Glazing Interior												
	Fabric		Fabric + Glazing Interior			Tv = Visible Light Transmittance %	Tuv = UV transmittance %	Direct Solar Transmittance				Ql = Secondary Heat Transfer Factor				Fabric + Glazing Interior				
	As = Solar Absorbance %	R <sub>s</sub> = Solar Reflectance %	T <sub>s</sub> = Solar Transmittance %	Glazing A - g <sub>v</sub> = 0.85 - U = 5.8	Glazing B - g <sub>v</sub> = 0.76 - U = 2.9			Glazing C - g <sub>v</sub> = 0.59 - U = 1.2	Glazing D - g <sub>v</sub> = 0.32 - U = 1.1	Glazing A - g <sub>v</sub> = 0.85 - U = 5.8	Glazing B - g <sub>v</sub> = 0.76 - U = 2.9	Glazing C - g <sub>v</sub> = 0.59 - U = 1.2	Glazing D - g <sub>v</sub> = 0.32 - U = 1.1	Glazing A - g <sub>v</sub> = 0.85 - U = 5.8	Glazing B - g <sub>v</sub> = 0.76 - U = 2.9	Glazing C - g <sub>v</sub> = 0.59 - U = 1.2	Glazing D - g <sub>v</sub> = 0.32 - U = 1.1	Sc = Shading Coefficient		
White	12.1	68.4	19.5	0.34	0.36	0.35	0.25	4.1	0.17	0.15	0.12	0.07	0.17	0.21	0.23	0.18	0.40	0.47	0.59	0.78
White Stone	25.7	55.4	18.9	0.41	0.42	0.39	0.26	7.1	0.16	0.14	0.11	0.06	0.25	0.28	0.28	0.20	0.49	0.56	0.66	0.81
White Grey	37.0	47.6	15.4	0.46	0.46	0.42	0.27	6.2	0.13	0.11	0.09	0.05	0.32	0.35	0.33	0.22	0.54	0.61	0.70	0.83
Grey	60.0	26.9	13.1	0.57	0.56	0.48	0.29	9.2	0.11	0.09	0.07	0.04	0.46	0.47	0.41	0.25	0.67	0.74	0.82	0.89
Charcoal Grey	80.6	10.9	8.5	0.66	0.64	0.53	0.30	7.9	0.07	0.06	0.04	0.02	0.59	0.58	0.49	0.28	0.78	0.85	0.90	0.94
Charcoal	90.1	3.5	6.4	0.70	0.68	0.56	0.31	6.4	0.05	0.04	0.03	0.02	0.65	0.64	0.53	0.29	0.82	0.89	0.94	0.96
White Linen	22.6	56.6	20.8	0.41	0.42	0.39	0.26	16.6	0.18	0.16	0.12	0.07	0.23	0.26	0.27	0.19	0.48	0.55	0.66	0.81
Linen	36.8	42.8	20.4	0.49	0.49	0.43	0.27	14.8	0.18	0.15	0.11	0.07	0.31	0.34	0.32	0.21	0.58	0.64	0.73	0.85
Charcoal Sand	79.2	12.4	8.4	0.65	0.64	0.53	0.30	7.8	0.07	0.06	0.04	0.02	0.58	0.58	0.49	0.27	0.77	0.84	0.90	0.93
Charcoal Apricot	76.9	13.5	9.6	0.65	0.63	0.53	0.30	8.8	0.08	0.07	0.05	0.03	0.57	0.56	0.48	0.27	0.76	0.83	0.89	0.93
Bronze	77.5	12.4	10.1	0.65	0.64	0.53	0.30	8.0	0.08	0.07	0.05	0.03	0.57	0.57	0.48	0.27	0.77	0.84	0.90	0.93
Charcoal Bronze	85.5	6.5	8.0	0.69	0.67	0.55	0.30	7.6	0.07	0.06	0.04	0.02	0.62	0.61	0.51	0.28	0.81	0.88	0.93	0.95



**Blindware Pty Ltd**  
 Unit 1/3 Dunlop Crt, Bayswater 3153 Tel: (03) 9876 0400  
 Fax: (03) 9720 2746  
 Email: sales@blindware.com.au  
 Web: www.blindware.com.au